Product information

Marine 4T Motor Oil 15W-40

PI 34/11/22/2023



High-performance motor oil based on selected base oils and modern additive technology. Developed specifically for the maritime requirements. Even in extreme conditions quarantees optimum lubrication and reliable protection against wear. The high proportion of corrosion inhibitor quarantees protection against rust and corrosion.

Properties

- high wear resistance
- tested for turbochargers and catalytic converters
- low evaporation loss
- high shear stability
- can be used in gasoline and diesel engines with and without turbocharger

Specifications / Approvals

ACEA A3/B4, E7 • API CI-4 • API SL • Mack EO-N • MTU Typ 2 • Renault Trucks RLD-2 • Volvo VDS-3

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Caterpillar ECF-1-a • Caterpillar ECF-2 • Cummins CES 20076 • Cummins CES 20077 • Cummins CES 20078 • Detroit Diesel • Deutz DQC III-10 • MAN M 3275-1

15W-40

Technical data

SAE class (engine oils)

| • | SAE J300 |
|---------------------------|----------------------------|
| Density at 15 °C | 0,875 g/cm³ DIN 51757 |
| Viscosity at 40 °C | 105,0 mm²/s ASTM D7042 |
| Viscosity at 100 °C | 14,5 mm²/s ASTM D7042 |
| Viscosity at -25 °C (MRV) | < 60000 mPas ASTM D4684 |
| Viscosity at -20 °C (CCS) | <= 7000 mPas ASTM D5293 |
| Viscosity index | 145 DIN ISO 2909 |
| HTHS at 150°C | >= 3,7 mPas |

ASTM D5481

-36 °C Pour point

DIN ISO 3016

Evaporation loss (Noack) 9.0 %

CEC-L-40-A-93

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de

Flash point 230 °C

DIN ISO 2592

Technical data

Total base number 10,5 mg KOH/g **DIN ISO 3771** Sulfate ash 1,0 - 1,6 g/100g DIN 51575 Color number (ASTM) 1 3.5 **DIN ISO 2049**

Areas of application

All-season oil for gasoline and diesel boat engines. Can be mixed with all commercially available motor

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed.

Available pack sizes

| 1 l Canister plastic | 25015 D-B00KLET |
|--------------------------|--------------------|
| 5 l Canister plastic | 25016 D-B00KLET |
| 20 l Canister plastic | 25061 D-GB |
| 60 l Black plate barrel | 25017 D-GB |
| 205 l Black plate barrel | 25018 D-GB |

Our information is based on thorough research and may be considered reliable, although not legally binding.