

# Sika<sup>®</sup> Remover-208

## Cleaning agent for surface preparation and removal of uncured adhesives and sealants

### Technical Product Data

Chemical base	Organic solvents
Colour	Colourless, clear
Density (CQP <sup>1</sup> 006-3 / ISO 2811-1)	0.80 kg/l approx.
Flash point (CQP 007-1 / ISO 13736)	24°C approx.
Application temperature <sup>2</sup>	5°C to 40°C
Application method	Wipe on, wipe off with lint free paper towel
Storage	Store in sealed container in a cool dry place below 25°C
Shelf life	24 months

<sup>1)</sup> CQP = Corporate Quality Procedure <sup>2)</sup> When applied at other temperatures contact Sika Industry Technical Service Dept.

### Description

Sika<sup>®</sup> Remover-208 is used to remove traces of Sikaflex<sup>®</sup> products as well as for cleaning painted substrates.

Sika<sup>®</sup> Remover-208 is manufactured in accordance with ISO 9001/14001, quality assurance system and with the responsible care program.

### Areas of Application

Sika<sup>®</sup> Remover-208 can be used to remove uncured excess material of Sikaflex<sup>®</sup> adhesive or sealant from application tools or from soiled surfaces.

Sika<sup>®</sup> Remover-208 can also be used for the pre-cleaning of strongly contaminated non-porous substrates.

Sika<sup>®</sup> Remover-208 can be used to clean painted surfaces prior to bonding.

This product is suitable for professional, experienced users only. Test with actual substrates and conditions have to be performed to ensure adhesion and material compatibility.

### Method of Application

*Removal of uncured adhesive*  
Remove the bulk of the Sikaflex<sup>®</sup> residue with a knife or spatula. Moisten a rag or towel with Sika<sup>®</sup> Remover<sup>®</sup>-208 and wipe off the remaining adhesive or sealant.

#### *Surface cleaning*

Wipe painted surfaces with a moistened rag or towel with Sika<sup>®</sup> Remover -208. Wet the paper towel by pouring the Sika<sup>®</sup> Remover 208 onto the cloth. Do not dip towel into the can as there is risk of contamination. Wipe the surface with the wetted paper towel. Use fresh paper towels regularly in order to maximize cleaning power and minimize re-contaminating surface.

Before the solvent evaporates, wipe off with a fresh, clean, dry paper towel. Repeat above process as necessary until no contaminant is visible on a clean paper towel.

Do not use on sensitive surfaces such as fresh paints, particularly one pack air drying paint systems. Reseal container immediately after use.



### Important Note

Discard any Sika® Remover-208 that has become contaminated.

### Further Information

Working instructions issued for a defined application may further specify technical data contained in this Product Data Sheet.

Copies of the following publications are available on request:

- Material Safety Data Sheets
- Sika Primer Chart

### Packaging Information

Can	1 litre
-----	---------

### Value Bases

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### Health and Safety Information

For information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Material Safety Data Sheets containing physical, ecological, toxicological and other safety-related data.

### Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Further information available at:  
[www.sika.co.uk](http://www.sika.co.uk)  
[www.sika.com](http://www.sika.com)

Sika Limited  
Industry  
Watchmead, Welwyn Garden City  
Hertfordshire, AL7 1BQ  
United Kingdom  
Tel: +44 (0)1707 394444  
Fax: +44 (0)1707 329129

